# **Internal Government Studies**

### 1995

# **Reports and Presentations**

**Study Name:** 

**Interferometer Thermal** 

Sounder [ITS] - Part II

**Team Members:** 

NOAA/ORA(Mitch Goldberg) &

NASA/GSFC(Joel Susskind)

**IPO POC:** 

D. Blersch

#### INTERNAL GOVERNMENT STUDIES - FY 1995 Interferometer Thermal Sounder [ITS] - Part II

Presentation/Paper Title	Author(s)	Date
"Final Report to the Integrated Program Office on the Interferomter Thermal Sounder Study: Part II	Susskind, McMillan, Goldberg	15 NOV 95
"IGS Final Presentations for FY95: Interferometer Thermal Sounder (ITS)-[PART II: ITS versus AIRS Tradeoff]"	Goldberg, McMillan, Susskind, Smith, Huang	29 SEPT 95
"IGS Final Presentations for FY95: Interferometer Thermal Sounder (ITS)-Comparative Study of Performance of ITS versus AIRS"	Goldberg, McMillan, Susskind, Smith, Huang	29 SEPT 95
"Interferometer Thermal [Sounder (ITS)-Part II ITS versus AIRS Tradeoff] - Midterm Presentations"	Goldberg, McMillan, Susskind, Smith, Huang	29 JUNE 95
"Primary Differences Between AIRS and ITS"	Joel Susskind	29 JUNE 95
"POES CARD Input for ITS-part II"	Mitch Goldberg	18 APRIL 95
"High Resolution Transmittance for ITS versus AIRS"	Larry McMillan	3 JULY 95
"Preliminary Report on ITS Simulation Study"	Joel Susskind	18 APRIL 95
"ICS Monthly Status Report on ITS"	Mitch Goldberg	18 APRIL 95

# Interferometer Thermal Sounder (ITS) [Part II ITS vs. AIRS Tradeoff]

#### 9/29/95

# **Participants:**

NOAA/ORA: M. Goldberg, L. McMillin

NASAIGSFC: 3. Susskind

CIMSS: W. Smith, A. Huang

#### **OBJECTIVE**

To evaluate the ability of the **proposed ITS** system design to meet temperature and moisture **profile** requirements specified in the **NPOESS** IORD and compare these results with other proposed sensors especially AIRS.

# Major tasks:

- 1) Establish radiative transfer models for ITS and AIRS.
- 2) Generate retrieval results for ITS and AIRS.
- 3) Assess the ability of the ITS to meet IORD requirements.

#### Task 1:

#### Establish radiative transfer models for ITS and AIRS

- Establish line by line transmittance database. ORA
- Acquire instrument specifications ORA
- Instrument dependent convolution or Fourier transform/construction of transmittance data for generation of fast models ORA
- Generation of instrument dependent fast transmittance model ORA

# **Accomplishments for Task 1:**

- software completed to generate, store, and retrieve transmittances at .01 cm-1 resolution.
- software completed to compute instrument radiances.
- software completed for fast transmittance algorithm for AIRS (spectrometer) and apodized interferometer data.
- obtained most of required hardware.

#### Task 2:

Generate retrieval results for ITS and AIRS.

- Generate simulated radiance datasets for retrieval algorithm ORA
- Retrieval performance comparison ORA/GSFC
- Information content analysis CIMSS

# **Accomplishments:**

- very little. Need to complete task 1.
- Procurement for CIMSS task was completed 8/95.
- retrieval software is in place.

# Task 3:

Assess the ability of the ITS to meet IORD retrieval accuracy requirements.

- Final report ORA/GSFC/CIMSS

# COMPARATIVE STUDY OF PERFORMANCE OF ITS VS AIRS

#### **OBJECTIVE**:

Assess effects of different instrumental characteristics on accuracy of retrieved products T(p), q(p)

# Significant differences between ITS and AIRS

## **Primary:**

Spectral characteristics

Response functions

AIRS narrow ( $v/\Delta v \approx 1200$ ) and localized (95% within  $\pm \Delta v$ )

ITS either too broad  $(v/\Delta v \approx 600)$  or non localized  $(\approx 40\% \text{ in } \pm \Delta v)$ 

Sampling

AIRS spectrally sampled twice as often as ITS

Domain

AIRS extends to shorter wavelengths

Signal to noise

Scene dependence of ITS noise

ITS much noisier than AIRS at short wavelengths

**Secondary**:


Field of view size

Contiguous (AIRS) vs sub-sampled (ITS)

Spatial coregistration between channels

Places tight constraint on image motion compensation for ITS

Study concentrates on primary issues



# SPECTRAL CHARACTERISTICS OF INTERFEROMETER

Measures interferogram of radiance spectrum I(x) for  $x = 0 \rightarrow L = max$  delay in cm

Spectral response for channel I  $f_I(v-v_I)$ 

 $f_I(v - v_I)$  = Fourier transform of A(x) I(x) where A(x) = apodization function A(x) = 1 called unapodized

 $f_I(v-v_I)$  is a function of L, A(x)


Increasing L makes  $f_I(v - v_I)$  narrower with width  $\approx \frac{1}{L}$ 


Unapodized response function ( $\approx \sin y/y$ ) has narrow central lobe but extended side lobes Central lobe contains  $\approx 40\%$  of total spectral response


### Ideally, want narrow central lobes without side lobes

Spectral resolution and spectral purity

Resolves and isolates spectral regions optimal for sounding Apodization can reduce side lobes while broadening central lobe







# POTENTIAL DRAWBACKS OF UNAPODIZED SPECTRAL FUNCTIONS

Must be able to compute radiances accurately with reasonable computation time Usual radiance approximation used for narrow band channels does not hold Current "exact" code uses monochromatic radiances  $\approx 1000$  times slower Need accurate approximation, reasonable computation time, for practical use

Must be able to account for response beyond central lobe to better than noise limits

Reduce effects of 4° RMS contamination to better than 0.2° noise

Potential problem - trace species contamination from distant lines

Retrieval algorithm may need many more channels to account for contamination AIRS algorithm uses  $\approx 200$  out of 2400 channels

For these reasons, unapodized spectra have not been used for retrievals

#### ORIGINAL STUDY PLAN FOR FY 95

- Perform detailed simulations of instrument observations, with noise
   Ensemble of clear and partially cloudy scenes
- Test effect of apodization on retrieval accuracy
- Perform independent retrievals by both NASA and NOAA
   Tests method dependence of results
   Make simulated data available for others to use as well
- Evaluate results

Does ITS meet NOAA sounding requirements?

Problem was more complex than originally thought

# ACCOMPLISHMENTS SINCE LAST MEETING

#### SMALL STEPS IN RIGHT DIRECTION

Formed in-house interferometer specialist team

Built IRIS and Cassini interferometers

Providing model to simulate observational noise

Noise computed based on instrument and scene characteristics

Will give independent check of Lincoln Lab estimates

- Developed in house expertise on use of appropriate apodization functions
- Wrote joint proposal to do complete end to end simulation study in FY 96

#### Comparative Performance Study of Interferometer vs. AIRS

submitted to

#### Integrated Program Office

#### Co-Principal Investigator

Dr. Joel Susskind NASA/GSFC, Code 910.4 301-286-7210

#### Co-Investigators

Dr. Chris Barnet NASA/GSFC, Code 910.4 301-286-2679

Dr. Donald Jennings NASA/GSFC, Code 693.2 301-286-7701

Mr. Lawrence Herath NASA/GSFC, Code 693.2 301-286-3874

#### Co-Principal Investigator

Dr. Mitch Goldberg NOAA/NESDIS/ORA 301-763-8136

#### Co-Investigator

Dr. Larry McMillin NOAA/NESDIS/ORA 301-763-8136

Dr. Joel Susskind

Co-Principal Investigator

Dr. Mitch Goldberg

Co-Principal Investigator

Starting Date: October 1, 1995

Support Requested: 10/95 - 9/96 \$300K

# MILESTONES

WILESTONES	
BY 1/31/96	Simulate instrument noise characteristics for ITS, IASI,
	Simulate apodized and unapodized spectra for ensemble of cases (clear, partially cloudy)
	Generate rapid algorithm for apodized and AIRS transmittance functions
3/30/96	Perform physical retrievals (NASA, NOAA separately) for clear and cloudy apodized spectra and AIRS spectra. Evaluate results
	Perform regression retrievals for unapodized spectra - NOAA only
6/30/96	Develop computationally efficient rapid algorithm for use with unapodized spectra (hard part)
9/30/96	Perform and evaluate clear and cloudy retrievals for unapodized spectra (NASA and NOAA)
	Have final report

# Task 3:

Assess the ability of the ITS to meet IORD retrieval accuracy requirements.

- Final report ORA/GSFC/CIMSS